



Frese a 3 taglienti per cave, serie extra corta**Langlochfräser 3-Schneiden extra kurz****N**

**Tipo N, ≈ 30° elica,
12° angolo di spoglia,
con codolo cilindrico
secondo DIN 1835/1**

Slot drills 3-fluted, extra short series
Type N, helix angle ≈ 30° rake angle 12°,
with straight shank acc. DIN 1835/1

**Typ N, ≈ 30° Drallwinkel,
12° Spanwinkel,
mit Zylinderschaft nach
DIN 1835/1**

Fraises à rainurer 3 dents, série extra courte
Type N, angle d'hélice ≈ 30°, angle
de coupe 12°, avec queue cylindrique
selon DIN 1835/1



DIN 327
HSS-Co8

HSS-Co8

HSS-Co8
TiN

HSS-Co8
TiCN

HSS-Co8
TiALN FUTURA®

Cat. Nr. - Kat. Nr. - Cat. no. - No. de cat.			3308	3310	3308T	3308C	3308F
Ød1 e8	l₂	l₁	Ød₂	Z			
16	19	79	16	3	●	●	●
16,7*	19	79	16	3	●	●	●
17*	19	79	16	3	●	●	●
17,7*	19	79	16	3	●	●	●
18	19	79	16	3	●	●	●
19*	19	79	16	3	●	●	●
19,7▲	22	88	20	3	●	●	●
20	22	88	20	3	●	●	●
21,7*	22	88	20	3	●	●	●
22	22	88	20	3	●	●	●
23,7	26	102	25	3	●	●	●
24	26	102	25	3	●	●	●
24,7*	26	102	25	3	●	●	●
25	26	102	25	3	●	●	●
26*	26	102	25	3	●	●	●
27,7*	26	102	25	3	●	●	●
28	26	102	25	3	●	●	●
29,7*	26	102	25	3	●	●	●
30*	26	102	25	3	●	●	●
32	32	112	32	3	●	●	●
34*	32	112	32	3	●	●	●
35*	32	112	32	3	●	●	●
36	32	112	32	3	●	●	●
40▲	38	118	32	3	●		
45▲	38	118	32	3	●		
50▲	45	125	32	3	●		

● Utensile disponibile a magazzino - Tool in stock - Werkzeug vorrätig ab Lager - Outil disponible à stock

* Tolleranza h 10 - Toleranz h 10 - Tolerance h 10 - Tolérance h 10

▲ ILLICO NORM