




Frese a 2 taglienti per cave, serie extra corta

Langlochfräser 2-Schneiden extra kurz



**Tipo N, $\approx 30^\circ$ elica,
10° angolo di spoglia,
con codolo cilindrico
secondo DIN 1835/1**




**Slot drills 2-fluted,
extra short series**

Type N, helix angle $\approx 30^\circ$ rake angle 10° ,
with straight shank acc. DIN 1835/1

**Typ N, $\approx 30^\circ$ Drallwinkel,
10° Spanwinkel,
mit Zylinderschaft nach
DIN 1835/1**

**Fraises à rainurer 2 dents,
série extra courte**

Type N, angle d'hélice $\approx 30^\circ$, angle de
coupe 10° , avec queue cylindrique selon
DIN 1835/1



**DIN 327
ASP-60**

- ASP-60
- ASP-60
TiN
- ASP-60
TiCN
- ASP-60
TiAlN FUTURA®

Cat. Nr. - Kat. Nr. - Cat. no. - No. de cat.					3220	3220T	3220C	3220F
$\varnothing d1$ e_8	l_2	l_1	$\varnothing d_2$	Z				
22	22	88	20	2	●	●	●	●
24	26	102	25	2	●	●	●	●
25	26	102	25	2	●	●	●	●

● Utensile disponibile a magazzino - Tool in stock - Werkzeug vorrätig ab lager - Outil disponible à stock

* Tolleranza h 10 - Toleranz h 10 - Tolerance h 10 - Tolérance h 10