

DIN 338**СВЕРЛА СРЕДНЕЙ ДЛИНЫ****Сверла с гладким цилиндрическим хвостовиком из быстрорежущей стали HSS**

Обозначение	6151	6151TN	6106	6187	6197	6210	6210TN	6210TC	6158	6190	6199	6209
Тип	N	N	NML	H	W	STL	STL	STL	N	H	W	STL
Направление вращения	↻	↻	↻	↻	↻	↻	↻	↻	↻	↻	↻	↻
Материал сверла	HSS	HSS	HSS	HSS	HSS	HSS	HSS	HSS	HSS	HSS	HSS	HSS
\varnothing , мм Ø, дюймы												
по ANSI*												
0,63	26	8	●	-	-	-	-	-	-	-	-	-
0,635	72	26	8	●	-	-	-	-	-	-	-	-
0,64	26	8	●	-	-	-	-	-	-	-	-	-
0,65	26	8	●	-	-	●	●	-	-	●	-	-
0,66	26	8	●	-	-	-	-	-	-	-	-	-
0,660	71	26	8	●	-	-	-	-	-	-	-	-
0,67	26	8	●	-	-	-	-	-	-	-	-	-
0,68	28	9	●	-	-	-	-	-	-	-	-	-
0,69	28	9	●	-	-	-	-	-	-	-	-	-
0,7	28	9	●	●	-	●	●	-	-	●	●	●
0,71	28	9	●	-	-	-	-	-	-	-	-	-
0,711	70	28	9	●	-	-	-	-	-	-	-	-
0,72	28	9	●	-	-	-	-	-	-	-	-	-
0,73	28	9	●	-	-	-	-	-	-	-	-	-
0,74	28	9	●	-	-	-	-	-	-	-	-	-
0,742	69	28	9	●	-	-	-	-	-	-	-	-
0,75	28	9	●	-	-	●	●	-	-	●	-	-
0,76	30	10	●	-	-	-	-	-	-	-	-	-
0,77	30	10	●	-	-	-	-	-	-	-	-	-
0,78	30	10	●	-	-	-	-	-	-	-	-	-
0,787	68	30	10	●	-	-	-	-	-	-	-	-
0,79	30	10	●	-	-	-	-	-	-	-	-	-
0,795	1/32	30	10	●	-	-	-	-	-	-	-	-
0,8	30	10	●	●	-	●	●	-	-	●	●	●
0,81	30	10	●	-	-	-	-	-	-	-	-	-
0,813	67	30	10	●	-	-	-	-	-	-	-	-
0,82	30	10	●	-	-	-	-	-	-	-	-	-
0,83	30	10	●	-	-	-	-	-	-	-	-	-
0,838	66	30	10	●	-	-	-	-	-	-	-	-
0,84	30	10	●	-	-	-	-	-	-	-	-	-
0,85	30	10	●	-	-	●	●	-	-	●	-	-
0,86	32	11	●	-	-	-	-	-	-	-	-	-

● В наличии на складе.

* Обозначение диаметра (литера или номер) по ANSI/ASME B 94.11 M.

3/20 ➤