



HAND-GEWINDEBOHRER / HAND TAPS

KAT.-NR. ITEM	SIMBOL SYMBOL	Ø mm	DIN	SACKLOCH / DURCHGANGSLOCH Blind hole/ Through hole	TOLERANZ TOLERANCE	DRALLWINKEL HELIX ANGLE	ANSCHNITT FORM CHAMFER FORM
<b>N</b>							
<b>6615</b> 	M	1 ÷ 68	352		6H	0°	C
<b>6608</b> Sätze in Metallkassetten Sets in metal cases with tap drills 	M	3 ÷ 12	352		6H	0°	C
<b>6609</b> Sätze in Metallkassetten Sets in metal cases with tap drills 	M	3 ÷ 12	352		6H	0°	C
<b>6618</b> 	M	3 ÷ 20	352		6H	0°	C
<b>6633</b> 	MF	2 ÷ 52	2181		6H	0°	C
<b>6775</b> 	UNC	1 ÷ 2	352*		2B	0°	C
<b>6776</b> 	UNF	3 ÷ 7/16	2181*		2B	0°	C
<b>6603</b> 	BSW/W	1/16 ÷ 2	352*		-	0°	C
<b>6627</b> 	BSP/G	1/16 ÷ 2	5157		-	0°	C