



MASCHINEN-GEWINDEBOHRER / MACHINE TAPS

KAT.-NR. ITEM	SIMBOL SYMBOL	Ø mm	DIN	SACKLOCH / DURCHGANGSLOCH Blind hole/ Through hole	TOLERANZ TOLERANCE	DRALLWINKEL HELIX ANGLE	ANSCHNITT FORM CHAMFER FORM
<b>RAPID</b>							
<b>6730</b> 	MF	3 ÷ 52	374		6H	0°	B
<b>6690</b> 	UNC	1 ÷ 3/8	2184/1		2B-3B	0°	B
<b>6693</b> 	UNC	7/16 ÷ 2	2184/1		2B-3B	0°	B
<b>6607</b> 	UNF	1 ÷ 3/8	2184/1		2B-3B	0°	B
<b>6687</b> 	UNF	7/16 ÷ 1 1/2	2184/1		2B-3B	0°	B
<b>6697</b> 	BSW/W	1/8 ÷ 3/8	371*		-	0°	B
<b>6636</b> 	BSW/W	7/16 ÷ 1x8	376*		-	0°	B
<b>6704</b> 	BSP/G	1/16 ÷ 2X11	5156		-	0°	B
<b>6673</b> 	RP	1/16 ÷ 2	5156		-	0°	B
<b>6710</b> 	PG	7 ÷ 48	40 432		-	0°	B

**RAPID 2**

<b>6640</b> 	M	2 ÷ 10	371		6H-6G	0°	B
-----------------	---	--------------	-----	--	-------	----	---

**N** ■ Gerade genutet / Straight Flutes

<b>6706</b> 	M	1 ÷ 10	371		6H	0°	C
<b>6705</b> 	M	2 ÷ 52	376		6H	0°	C
<b>6726</b> 	MF	3 ÷ 52	374		6H	0°	C
<b>6823</b> 	UNC	3 ÷ 3/8	2184/1		2B	0°	C