


# DIN 206 A/B



## Hand-Reibahlen aus HSS für Bohrungen mit Passung H7

Hand reamers made of HSS  
to produce holes with H7 tolerances



Form / Form			A	B
Typ / Type			Schneiden gerade straight	Schneiden 7/8° LH
Schneidrichtung Cutting direction				
Schneidstoff Material			HSS	HSS
Ø mm	l <sub>1</sub> mm	l <sub>2</sub> mm	6301	6302
8,6	124	62	●	●
8,7	124	62	●	●
8,8	124	62	●	●
8,9	124	62	●	●
9,0	124	62	●	●
9,1	124	62	●	●
9,2	124	62	●	●
9,3	124	62	●	●
9,4	124	62	●	●
9,5	124	62	●	●
9,6	133	66	●	●
9,7	133	66	●	●
9,8	133	66	●	●
9,9	133	66	●	●
10,0	133	66	●	●
10,1	133	66	●	-
10,2	133	66	●	-
10,3	133	66	●	-
10,4	133	66	●	-
10,5	133	66	●	●
10,6	133	66	●	-
10,7	142	71	●	-
10,8	142	71	●	-
10,9	142	71	●	-
11,0	142	71	●	●
11,1	142	71	●	-
11,2	142	71	●	-
11,3	142	71	●	-
11,4	142	71	●	-
11,5	142	71	●	●
11,6	142	71	●	-
11,7	142	71	●	-
11,8	142	71	●	-
11,9	152	76	●	-
12,0	152	76	●	●
12,5	152	76	●	-
13,0	152	76	●	-
13,5	163	81	●	-

Form / Form			A	B
Typ / Type			Schneiden gerade straight	Schneiden 7/8° LH
Schneidrichtung Cutting direction				
Schneidstoff Material			HSS	HSS
Ø mm	l <sub>1</sub> mm	l <sub>2</sub> mm	6301	6302
14,0	163	81	●	●
14,5	163	81	●	●
15,0	163	81	●	●
15,5	175	87	●	●
16,0	175	87	●	●
16,5	175	87	●	●
17,0	175	87	●	●
17,5	188	93	●	●
18,0	188	93	●	●
18,5	188	93	●	●
19,0	188	93	●	●
19,5	201	100	●	●
20,0	201	100	●	●
20,5	201	100	●	●
21,0	201	100	●	●
21,5	201	100	●	●
22,0	215	107	●	●
22,5	215	107	●	●
23,0	215	107	●	●
23,5	215	107	●	●
24,0	231	115	●	●
24,5	231	115	-	●
25,0	231	115	●	●
25,5	231	115	●	●
26,0	231	115	●	●
26,5	231	115	●	●
27,0	247	124	●	●
27,5	247	124	-	●
28,0	247	124	●	●
28,5	247	124	●	●
29,0	247	124	●	●
29,5	247	124	●	●
30,0	247	124	●	■
31,0	265	133	●	●
32,0	265	133	●	●
33,0	265	133	●	●
34,0	284	142	●	●
35,0	284	142	●	●

● Standardartikel / Items available ex stock ■ Auslaufender Artikel / discontinued items