

TECHNISCHE DATEN

TECHNICAL DATA



664		664		664		666		666		666		666					
2179		2180		ILIX NORM.								60-011		331			
												E		B			
HSS		HSS		HSS		HSS		HSS		HSS		HSS		HSS			
45°		45°		0°		0°		7/8°		45°		25°					
BL		BL		BL		BL		BL		BL		BL		BL			
-		-		-		-		-		-		-		-			
6313		6314		6308		6310		6311		6319		6355					
VC	F*	VC	F*	VC	F*	VC	F*	VC	F*	VC	F*	VC	F*	VC	F*		
10	1.0	10	1.0	10	1.0	10	1.0	10	1.0	10	1.0	10	1.0	10	1.0		
6	0.8	6	0.8	6	0.8	6	0.8	6	0.8	6	0.8	6	0.8	6	0.8		
4	0.6	4	0.6	4	0.6	4	0.6	4	0.6	4	0.6	4	0.6	4	0.6		
3	0.8	3	0.8	3	0.8	3	0.8	3	0.8	3	0.8	3	0.8	3	0.8		
2	0.6	2	0.6	2	0.6	2	0.6	2	0.6	2	0.6	2	0.6	2	0.6		
10	1.1	10	1.1	10	1.1	10	1.1	10	1.1	10	1.1	10	1.1	10	1.1		
6	1.2	6	1.2	6	1.2	6	1.2	6	1.2	6	1.2	6	1.2	6	1.2		
13	1.6	13	1.6	13	1.6	13	1.6	13	1.6	13	1.6	13	1.6	13	1.6		
8	1.4	8	1.4	8	1.4	8	1.4	8	1.4	8	1.4	8	1.4	8	1.4		
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		