




СВЕРЛА С УНИФИЦИРОВАННЫМ ХВОСТОВИКОМ ПО DIN 6535 НА

Высокопроизводительные укороченные сверла из быстрорежущей стали HSS-Co

Record Evolution VA



Обозначение					6134TN
Тип					
Направление вращения					
Материал сверла					HSS-Co
Ø h8, мм	l ₁ , мм	l ₂ , мм	d ₂ , мм		
10,30	89	43	10	●	
10,40	89	43	10	●	
10,50	89	43	10	●	
10,60	89	43	12	●	
10,70	95	47	12	●	
10,80	95	47	12	●	
10,90	95	47	12	●	
11,00	95	47	12	●	
11,10	95	47	12	●	
11,20	95	47	12	●	
11,30	95	47	12	●	
11,40	95	47	12	●	
11,50	95	47	12	●	
11,60	95	47	12	●	
11,70	95	47	12	●	
11,80	95	47	12	●	
11,90	102	51	12	●	
12,00	102	51	12	●	
12,10	102	51	12	●	
12,20	102	51	12	●	
12,30	102	51	12	●	
12,40	102	51	12	●	
12,50	102	51	12	●	
12,60	102	51	12	●	
12,70	102	51	12	●	
12,80	102	51	12	●	
12,90	102	51	12	●	
13,00	102	51	12	●	
13,50	107	54	16	●	
14,00	107	54	16	●	
14,50	111	56	16	●	

[illegible]

● Наличие на складе.